

GOVERNMENT

Swiftpro K60 Double Sided

Retransfer Card Printer

Swiftpro provides market-leading solutions with an extensive range of retransfer desktop solutions to meet the needs of the customer and by adding value to global businesses. Our mission is to revolutionize business identity and access management by building trusted partnerships through our simple SMART™ partner distribution networks.

The Swiftpro K60 retransfer card printer has an outstanding print quality for single and double sided printing. With 600dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management.

The ultra-fast, powerful Swiftpro K60 printer is available with contact and contactless smart card encoding technologies and 100-card input and output hoppers, with an optional 250-card input hopper upgrade. This reliable and durable printer is the ideal solution for both entry level to advanced secure card programs for a range of vertical markets.

Selecting the right printer is important. Equally if not more important is using Genuine Swiftpro Supplies. They are critical to delivering printer reliability, print quality and vibrant colors for your card programs. Swiftpro supplies deliver consistency and ensure the longevity of your printer and print head and minimize downtime and create efficiencies in your card programs. Always ask for Genuine Swiftpro Supplies from your Authorized Premiere Value Added Distributor,

Premiere Enterprise Solution Provider or Premiere Value-Added Reseller.



SECURITY

The ribbon erase function prevents leakage of personal information on the monochrome black panel ink ribbon. It scrambles information beyond recognition to protect this data.



VERSATILITY

Swiftpro's modular design permits customers to upgrade as their card programs need changes.



IMAGE QUALITY

High Resolution printing using 600dpi printing provides superior print quality for all your card programs.



RELIABILITY

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.



INNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organizations since 1989.



IGENTITY CARD

ARMICCECUEDE

DURABILITY

Highly durable printers with industry leading warranties on all our products and lifetime on the print head.



Printing

Dye Sublimation Retransfer

Full Color Retransfer

printing Single and Double Sided Printing

Up to 130 Cards Per Hour (YMCK) up to 70 Cards Per Hour (YMCK)

256 Gradation Printing

Over the Edge Printing on CR80, ID-1 Cards

Standard Features

USB & Ethernet connectivity

100-Card Input Hopper

(30mil) 100-Card Output

Hopper (30mil) LCD Panel

600 DPI Print Resolution

36 Month Printer Warranty

Lifetime Printhead

Warranty Microsoft Certified Drivers

Solenoid ElectronicLock for Card Input

Hopper

Solenoid ElectronicLock for Supplies / Front

Door Housing Software-controlled Lock/

Unlock from StatusMonitor KRibbon Erase

Function

IpSec Security for Secure Data Encryption IPv6

and IPv4 Inline Bend Remedy

MACAddress Forced Printing (UVPanel on Card) Kensington Lock



Technical Support: support@unicard.com.au Sales:sales@unicard.com.au |Ph: (02) 9437 1777 www.unicard.com.au

Encoding

Magnetic Stripe ISOHigh/Low Coercivity Encoder
Contactless Encoder, Omnikey 5127 (iClass, Mifare
and Desfire) Contact Encoder (CF-7CRW / Control

board)

Contact Encoder (CF-7CCS/ ICContact Station)

CardPresso

Card Exchange

All Card Personalizations software used through Swiftpro Driver*

*check with Software vendor, as some features may be limited for use on Swiftpro Printers

Microsoft® Windows®7, 8, 10 32bit /

64bit Microsoft® Windows® Server 2008

R2 (SP1) 64bit Microsoft®

Windows®XPServer 2012 64bit

YMCK-1000 Yield YMCKK-750 Yield

YMCKPPeel Off Ribbon - 750

Yield YMCKU UV-750 - Yield

InTM Retransfer Film - 1000 Yield

Height	13.19 in	(335 mm)With	nout	Card
S t	а	С	k	е	r
Width	13.5 in (343 mm) Without				Card
S t	а	C	k	е	r
Depth	12.68 in (322 mm) Without			Card	
S t	а	С	k	е	
Weight	29.76 lb	(13.5 kg)			

Interface

USB 2.0 (Hi-speed / Full Speed) Ethernet (100BASE-TX/ 10BASE-T)

Options

Flipper Unit Bend Remedy

Temperature: 59°Fto 86°F(15°Cto 30°C

Humidity: 35%to 70%(YMCKink, No

Condensation) 3.5A (110Vsystem) 1.6A

(220Vsystem)

310W (maximum power when all

optionsare installed)

Card Thickness 10-40mil

Card Size ISO 7810 Format, CR80,

ID-1 Card Material: PVC, PC, PET, PET-G

Technology Cards Contact and or Contactless with and Without Mag Stripe

